



STRUCTURE

MODULES		PUNTO GELATO
LENGHT	[mm]	2620
HEIGHT	[mm]	1003
DEPTH	[mm]	1520
END SIDE PANELS THICKNESS	[mm]	-
WEIGHT	(kg)	480
POSSIBILITY TO JOIN WITH OTHER MODULES		-
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM
GLASS STRUCTURE		-
TRAY HOLDER		-
WHEELS		OP.
SLIDING DOORS		-
CURTAIN		-
LIGHT		NEON/LED

GELATO

MODULES		PUNTO GELATO
PAN DEPTH FROM - TO	[mm]	120 - 150
PAN 360*165	[nr]	-
PAN 360*250	[nr]	-
PAN 260*160	[nr]	-
PAN 180*160	[nr]	-
TRAPEZOIDAL PANS	[nr]	12-15-18
OPERATOR GLASS		DOUBLE HEATED
CUSTOMER GLASS		DOUBLE HEATED
FLAVOUR MARKERS		X
SCOOP WASHER		OP.
CONTROL PANEL		ELECTRONIC THERMOSTAT
4 SEASONS VERSION (POS / NEG TEMP)		OP.
DIFFERENCIATE TEMPERATURE		-
COOLING SYSTEM		VENTILATED

AIR FLOW TYPE AND DIRECTION		SINGLE FROM EXTERNAL TO INTERNAL PEREMETER
EVAPORATOR		2
COMPRESSOR TYPE		HERMETIC
CONDENSATION TYPE		AIR
DEFROSTING TYPE		HOT GAS
EXTERNAL CONDENSATE DRAIN		OP.
CONDENSATE PAN		X
REMOTE COMPRESSOR TYPE		SEMI-HERMETIC
CONDENSATION TYPE		AIR, WATER, AIR-WATER MIXED
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES
OIL SEPARATOR		OP.
CE - GOST CERTIFICATION		X
CE - GOST POWER SUPPLY	V/ph/Hz	X
ETL SAFETY SANITATION CERTIFICATION		X
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60
WORKING TEMPERATURE		75 DEGREE F; 55% RH
CLIMATIC CLASS		35°C 60% RH