

# AKTIVA



## STRUCTURE

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
LENGTH	[mm]	1100	1600	2100	3200	1512	1518	1555	
HEIGHT	[mm]	1351 - 1436					1351		
DEPTH	[mm]	1168					1143	1143	1143
END SIDE PANELS THICKNESS	[mm]	45							
WEIGHT	(kg)	240	335	425	550	325	325	325	
POSSIBILITY TO JOIN WITH OTHER MODULES		X							
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM							
GLASS STRUCTURE		ALUMINIUM FINISH ( GOLD OPTIONAL ) - GLASS OPEN BOTTOM-UP							
TRAY HOLDER		-							
WHEELS		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
SLIDING DOORS		X	X	X	X	X	X	X	
CURTAIN		OP.	OP.	OP.	OP.	-	-	-	
LIGHT		NEON/LED							

## GELATO

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
PAN DEPTH FROM - TO	[mm]	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	
PAN 360*165	[nr]	12	18	24	36	11	12	12	
PAN 360*250	[nr]	8	12	16	24	7	7	7	
PAN 260*160	[nr]	-	-	-	-	-	-	-	
PAN 180*160	[nr]	-	-	-	-	-	-	-	
TRAPEZOIDAL PANS	[nr]	-	-	-	-	13	13	12	
FRONT GLASS		DOUBLE HEATED							
LATERAL GLASS		DOUBLE HEATED							
FLAVOUR MARKERS		LED ILLUMINATED							
SCOOP WASHER		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
CONTROL PANEL		ELECTRONIC THERMOSTAT							
4 SEASONS VERSION ( POS / NEG TEMP )		OP.	OP.	OP.	OP.	-	-	-	
DIFFERENCIATE TEMPERATURE		3+3	3+3	3+3	9+9	-	-	-	
COOLING SYSTEM		VENTILATED							
AIR FLOW TYPE AND DIRECTION		SINGLE FROM OPERATOR TO CUSTOMER SIDE							
EVAPORATOR	[nr]	2							
COMPRESSOR TYPE		HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC	HERMETIC	HERMETIC	HERMETIC	
CONDENSATION TYPE		AIR							
DEFROSTING TYPE		HOT GAS			REVERSE CYCLE	HOT GAS			
EXTERNAL CONDENSATE DRAIN		X	X	X	X	X	X	X	
CONDENSATE PAN		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
REMOTE COMPRESSOR TYPE		SEMI-HERMETIC							
CONDENSATION TYPE		AIR, WATER, MIXED AIR-WATER							
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES							
OIL SEPARATOR		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
CE - GOST CERTIFICATION		X	X	X	X	X	X	X	
CE - GOST POWER SUPPLY	V/ph/Hz	X							
ETL SAFETY SANITATION CERTIFICATION		X	X	X		X	X	X	
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60				-	208-220/1/60		
WORKING TEMPERATURE		75 DEGREE; 55% RH							
CLIMATIC CLASS		35°C 60% UR							

## PASTRY / DELI

MODULES		110	160	210	320	A1-30	A2-30	A2-45
REFRIGERATED FIX DISPLAY SHELF		X	X	X	X	X	X	X
NEUTRAL FIX DISPLAY SHELF		X	X	X	X	X	X	X
DRAWERS DISPLAY SHELF		X	X	X	X	-	-	-
LOWER LEVEL DISPLAY SHELF		-						
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
HOT SHELVES		OP.						
LIGHT COOLING SYSTEM		CHILLER						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
COOLING SYSTEM		VENTILATED						
EVAPORATOR	[nr]	1						
COMPRESSOR TYPE		HERMETIC						
CONDENSATION TYPE		AIR						
DEFROSTING TYPE		AT STOP						

EXTERNAL CONDENSATE DRAIN		X	X	X	X	X	X	X
CONDENSATE PAN		OP.	OP.	OP.	OP.	OP.	OP.	OP.
REMOTE COMPRESSOR TYPE		HERMETIC						
CONDENSATION TYPE		AIR						
DEFROSTING TYPE		AT STOP						
CE - GOST CERTIFICATION		X	X	X	X	X	X	X
CE - GOST POWER SUPPLY	V/ph/Hz	X						
ETL SAFETY SANITATION CERTIFICATION		X	X	X		X	X	X
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60				115/1/60		
WORKING TEMPERATURE		75 DEGREE; 55% RH						
CLIMATIC CLASS		35°C 60% UR						

### PASTRY WITH REFRIGERATED SHELVES H=1351 ONLY

MODULES		110	160	210	320	A1-30	A2-30	A2-45
REFR. FIX DISPLAY SHELF FOR REFR SHELVES		X	X	X	-	-	-	-
FRONT GLASS		DOUBLE HEATED						
LATERAL GLASS		DOUBLE HEATED						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
COOLING SYSTEM		VENTILATED WITH AIR FLOW REGULATION FOR SHELVES						
EVAPORATOR	[nr]	1						
COMPRESSOR TYPE		HERMETIC						
CONDENSATION TYPE		AIR						
DEFROSTING TYPE		HOT GAS						
EXTERNAL CONDENSATE DRAIN		X	X	X	-	-	-	-
CONDENSATE PAN		-	-	-	-	-	-	-
REMOTE COMPRESSOR TYPE		HERMETIC						
CONDENSATION TYPE		AIR						
DEFROSTING TYPE		HOT GAS 3 PIPES						
CE - GOST CERTIFICATION		X	X	X	-	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	X						
ETL SAFETY SANITATION CERTIFICATION		X	X	X	-	-	-	-
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60						
WORKING TEMPERATURE		75 DEGREE; 55% RH						
CLIMATIC CLASS		35°C 60% UR						

### PRALINES

MODULES		110	160	210	320	A1-30	A2-30	A2-45
REFRIGERATED FIX DISPLAY SHELF		X	X	X	-	-	-	-
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
LIGHT COOLING SYSTEM		CHILLER						
CONTROL PANEL		ELECTRONIC THERMOSTAT WITH HUMIDITY SENSOR						
COOLING SYSTEM		VENTILATED						
EVAPORATOR		1						
COMPRESSOR TYPE		HERMETIC						
CONDENSATION TYPE		AIR						
DEFROSTING TYPE		AT STOP						
EXTERNAL CONDENSATE DRAIN		X	X	X	-	-	-	-
CONDENSATE PAN		OP.	OP.	OP.	-	-	-	-
REMOTE COMPRESSOR TYPE		-	-	-	-	-	-	-
CONDENSATION TYPE		-	-	-	-	-	-	-
DEFROSTING TYPE		-	-	-	-	-	-	-
CE - GOST CERTIFICATION		X	X	X	-	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	X						
WORKING TEMPERATURE		75 DEGREE; 55% RH						
CLIMATIC CLASS		35°C 60% UR						

### DRY HOT

MODULES		110	160	210	-	-	-	-
HEATED DISPLAY SHELF		X	X	X	-	-	-	-
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
HALOGEN LAMPS		OP.						
HOT SHELVES		OP.						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
CE - GOST CERTIFICATION		X	X	X	X	X	X	X
CE - GOST POWER SUPPLY	V/ph/Hz	220/1/60						
WORKING TEMPERATURE		+65°C						

### BAIN-MARIE

MODULES		110	160	210	-	-	-	-
PANS	[nr]	3*1/1	4*1/1+2*1/4	6*1/1	-	-	-	-
PAN DEPTH	[mm]	150						
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
HALOGEN LAMPS		OP.						
HOT SHELVES		OP.						
WATER IN AND OUT		MANUAL						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
CE - GOST CERTIFICATION		X	X	X	-	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	220/1/60						
WORKING TEMPERATURE		+65°C						