

# CUBIKA



## STRUCTURE

MODULES		110	160	210	320	A1-30	A2-30	A2-45
LENGHT	[mm]	1100	1600	2100	3200	1571	1596	1643
HEIGHT	[mm]	1151 - 1351						
DEPTH	[mm]	1119				1257	1259	1269
END SIDE PANELS THICKNESS	[mm]					30		
WEIGHT	(kg)	240	335	425	550	325	325	325
POSSIBILITY TO JOIN WITH OTHER MODULES		X						
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM						
GLASS STRUCTURE		SHINY ALUMINIUM FINISH - GLASS OPEN BOTTOM-UP FOR H=1351, TOP GLASS OPEN FOR H=1151						
TRAY HOLDER		-						
WHEELS		OP.	OP.	OP.	OP.	OP.	OP.	OP.
SLIDING DOORS		X	X	X	X	X	X	X
CURTAIN		OP.	OP.	OP.	OP.	-	-	-
LIGHT		LED						

## GELATO

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
PAN DEPTH FROM - TO	[mm]	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	80 - 150	
PAN 360*165	[nr]	12	18	24	36	11	12	12	
PAN 360*250	[nr]	8	12	16	24	7	7	7	
PAN 260*160	[nr]	-	-	-	-	-	-	-	
PAN 180*160	[nr]	-	-	-	-	-	-	-	
TRAPEZOIDAL PANS	[nr]	-	-	-	-	13	13	12	
FRONT GLASS		DOUBLE HEATED							
LATERAL GLASS		DOUBLE HEATED							
FLAVOUR MARKERS		LED ILLUMINATED							
SCOOP WASHER		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
CONTROL PANEL		ELECTRONIC THERMOSTAT							
4 SEASONS VERSION ( POS / NEG TEMP )		OP.	OP.	OP.	OP.	-	-	-	
DIFFERENCIATE TEMPERATURE		3+3	3+3	3+3	9+9	-	-	-	
COOLING SYSTEM		VENTILATED							
AIR FLOW TYPE AND DIRECTION		SINGLE FROM OPERATOR TO CUSTOMER SIDE							
EVAPORATOR		2							
COMPRESSOR TYPE		HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC	HERMETIC	HERMETIC	HERMETIC	
CONDENSATION TYPE		AIR				AIR			
DEFROSTING TYPE		HOT GAS				REVERSE CYCLE		HOT GAS	
EXTERNAL CONDENSATE DRAIN		X	X	X	X	X	X	X	
CONDENSATE PAN		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
REMOTE COMPRESSOR TYPE		SEMI-HERMETIC							
CONDENSATION TYPE		AIR, WATER, MIXED AIR-WATER							
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES							
OIL SEPARATOR		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
CE - GOST CERTIFICATION		X	X	X	X	X	X	X	
CE - GOST POWER SUPPLY	V/ph/Hz	X							
ETL SAFETY SANITATION CERTIFICATION		X	X	X	X	X	X	X	

ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60	-	208-220/1/60
WORKING TEMPERATURE		75% DEGREE F: 55% RH		
CLIMATIC CLASS		35°C 60% UR		

### PASTRY / DELI

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
REFRIGERATED FIX DISPLAY SHELF		X	X	X	X	X	X	X	
NEUTRAL FIX DISPLAY SHELF		X	X	X	X	X	X	X	
DRAWERS DISPLAY SHELF		X	X	X	X	-	-	-	
LOWER LEVEL DISPLAY SHELF					-				
FRONT GLASS					DOUBLE				
LATERAL GLASS					DOUBLE				
HOT SHELVES					OP.				
LIGHT COOLING SYSTEM					-				
CONTROL PANEL					ELECTRONIC THERMOSTAT				
COOLING SYSTEM					VENTILATED				
EVAPORATOR					1				
COMPRESSOR TYPE					HERMETIC				
CONDENSATION TYPE					AIR				
DEFROSTING TYPE					AT STOP				
EXTERNAL CONDENSATE DRAIN		X	X	X	X	X	X	X	
CONDENSATE PAN		OP.	OP.	OP.	OP.	OP.	OP.	OP.	
REMOTE COMPRESSOR TYPE					HERMETIC				
CONDENSATION TYPE					AIR				
DEFROSTING TYPE					AT STOP				
CE - GOST CERTIFICATION		X	X	X	X	X	X	X	
CE - GOST POWER SUPPLY	V/ph/Hz				X				
ETL SAFETY SANITATION CERTIFICATION		X	X	X		X	X	X	
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60				115/1/60			
WORKING TEMPERATURE					75 DEGREE F: 55% RH				
CLIMATIC CLASS					35°C 60% UR				

### PASTRY WITH REFRIGERATED SHELVES H=1351 ONLY

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
REFR. FIX DISPLAY SHELF FOR REFR SHELVES		X	X	X	-	-	-	-	
FRONT GLASS					DOUBLE HEATED				
LATERAL GLASS					DOUBLE HEATED				
CONTROL PANEL					ELECTRONIC THERMOSTAT				
COOLING SYSTEM					VENTILATED WITH AIR FLOW REGULATION FOR SHELVES				
EVAPORATOR					1				
COMPRESSOR TYPE					HERMETIC				
CONDENSATION TYPE					AIR				
DEFROSTING TYPE					HOT GAS				
EXTERNAL CONDENSATE DRAIN		X	X	X	-	-	-	-	
CONDENSATE PAN		-	-	-	-	-	-	-	
REMOTE COMPRESSOR TYPE					HERMETIC				
CONDENSATION TYPE					AIR				
DEFROSTING TYPE					HOT GAS 3 PIPES				
CE - GOST CERTIFICATION		X	X	X	-	-	-	-	
CE - GOST POWER SUPPLY	V/ph/Hz				X				
ETL SAFETY SANITATION CERTIFICATION		X	X	X	-	-	-	-	
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60							
WORKING TEMPERATURE					75 DEGREE F: 55% RH				
CLIMATIC CLASS					35°C 60% UR				

### PRALINES

MODULES		110	160	210	320	A1-30	A2-30	A2-45	
REFRIGERATED FIX DISPLAY SHELF		X	X	X	-	-	-	-	
FRONT GLASS					DOUBLE				
LATERAL GLASS					DOUBLE				
LIGHT COOLING SYSTEM					-				
CONTROL PANEL					ELECTRONIC THERMOSTAT WITH HUMIDITY SENSOR				
COOLING SYSTEM					VENTILATED				
EVAPORATOR					1				
COMPRESSOR TYPE					HERMETIC				
CONDENSATION TYPE					AIR				
DEFROSTING TYPE					AT STOP				
EXTERNAL CONDENSATE DRAIN		X	X	X	-	-	-	-	
CONDENSATE PAN		OP.	OP.	OP.	-	-	-	-	
REMOTE COMPRESSOR TYPE		-	-	-	-	-	-	-	
CONDENSATION TYPE		-	-	-	-	-	-	-	
DEFROSTING TYPE		-	-	-	-	-	-	-	
CE - GOST CERTIFICATION		X	X	X	-	-	-	-	
ETL SAFETY SANITATION CERTIFICATION	V/ph/Hz				115/1/60				

WORKING TEMPERATURE		75 DEGREE F: 55% RH						
CLIMATIC CLASS		35°C 60% UR						

**DRY HOT (HEIGHT 1351CM only)**

MODULES		110	160	210	-	-	-	-
HEATED DISPLAY SHELF		X	X	X	-	-	-	-
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
HALOGEN LAMPS		OP.						
HOT SHELVES		OP.						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
CE - GOST CERTIFICATION		X	X	X	X	X	X	X
ETL SAFETY SANITATION CERTIFICATION	V/ph/Hz	220/1/60						
WORKING TEMPERATURE		+65°C						

**BAIN-MARIE (HEIGHT 1351CM only)**

MODULES		110	160	210	-	-	-	-
PANS		3*1/1	4*1/1+2*1/4	6*1/1	-	-	-	-
PAN DEPTH	[mm]	150						
FRONT GLASS		DOUBLE						
LATERAL GLASS		DOUBLE						
HALOGEN LAMPS		OP.						
HOT SHELVES		OP.						
WATER IN AND OUT		MANUAL						
CONTROL PANEL		ELECTRONIC THERMOSTAT						
CE - GOST CERTIFICATION		X	X	X	-	-	-	-
ETL SAFETY SANITATION CERTIFICATION	V/ph/Hz	220/1/60						
WORKING TEMPERATURE		+65°C						