



MODULES	
LENGHT	
HEIGHT	
DEPTH	
END SIDE PANELS THICKNESS	
WEIGHT	

200	M2-90
2000	1840
ISHING TYPE	
215	185

POSSIBILITY TO JOIN WITH OTHER MODULES							X
TANK							FOAM PANELS
GLASS STRUCTURE							NO, FIX OR OPEN UP-BOTTOM
TRAY HOLDER							-
WHEELS		OP.	OP.	OP.	OP.	OP.	
SLIDING DOORS		X	X	X	X	X	
CURTAIN		-	-	-	-	-	
LIGHT							NEON

GELATO

MODULES		100	125	150	200	M2-90
PAN DEPTH FROM - TO	[mm]	80 - 2*120	-	80 - 2*120	80 - 2*120	-
PAN 360*165	[nr]	5	-	8	11	-
PAN 360*250	[nr]	-	-	-	-	-
PAN 260*160	[nr]	-	-	-	-	-
PAN 180*160	[nr]	-	-	-	-	-
TRAPEZOIDAL PANS	[nr]	-	-	-	-	-
FRONT GLASS						SINGLE
LATERAL GLASS						SINGLE
FLAVOUR MARKERS						NO
SCOOP WASHER		OP.	-	OP.	OP.	-
CONTROL PANEL						ELECTRONIC THERMOSTAT
4 SEASONS VERSION (POS / NEG TEMP)		-	-	-	-	-
DIFFERENCIATE TEMPERATURE		-	-	-	-	-
COOLING SYSTEM						VENTILATED
AIR FLOW TYPE AND DIRECTION						SINGLE FROM THE OPERATOR TO THE CUSTOMER SIDE
EVAPORATOR						1
COMPRESSOR TYPE		HERMETIC	-	HERMETIC	HERMETIC	-
CONDENSATION TYPE						AIR

DEFROSTING TYPE		HOT GAS	-	HOT GAS	HOT GAS	-
EXTERNAL CONDENSATE DRAIN		X	-	X	X	-
CONDENSATE PAN		OP.	-	OP.	OP.	-
REMOTE COMPRESSOR TYPE		HERMETIC				
CONDENSATION TYPE		AIR, WATER, AIR-WTER MIXED				
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES				
OIL SEPARATOR		OP.	-	OP.	OP.	-
CE - GOST CERTIFICATION		X	-	X	X	-
CE - GOST POWER SUPPLY	V/ph/Hz	X				
ETL SAFETY SANITATION CERTIFICATION		X	-	X	X	-
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60				
WORKING TEMPERATURE		75 DEGREE F; 55% RH				
CLIMATIC CLASS		35°C 60% UR				

PASTRY / DELI

MODULES		100	125	150	200	M2-90
REFRIGERATED FIX DISPLAY SHELF		X	X	X	X	X
NEUTRAL FIX DISPLAY SHELF		X	X	X	X	X
DRAWERS DISPLAY SHELF		-	-	-	-	-
LOWER LEVEL DISPLAY SHELF		-				
FRONT GLASS		SINGLE				
LATERAL GLASS		SINGLE				
HOT SHELVES		OP.				
LIGHT COOLING SYSTEM		-				
CONTROL PANEL		ELECTRONIC THERMOSTAT				
COOLING SYSTEM		STATIC				
EVAPORATOR		1				
COMPRESSOR TYPE		HERMETIC				
CONDENSATION TYPE		AIR				
DEFROSTING TYPE		ELECTRIC				
EXTERNAL CONDENSATE DRAIN		OP.	OP.	OP.	OP.	OP.
CONDENSATE PAN		X	X	X	X	X
REMOTE COMPRESSOR TYPE		HERMETIC				
CONDENSATION TYPE		AIR				
DEFROSTING TYPE		ELECTRIC				
CE - GOST CERTIFICATION		X	X	X	X	X
CE - GOST POWER SUPPLY	V/ph/Hz	X				
ETL SAFETY SANITATION CERTIFICATION		X	X	X	X	-
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60				
WORKING TEMPERATURE		75 DEGREE F; 55% RH				
CLIMATIC CLASS		32°C 60% UR				

PASTRY DELI WITH SHELVES

MODULES		-	125	150	200	-
REFRIGERATED FIX DISPLAY SHELF		-	X	X	X	-
NEUTRAL FIX DISPLAY SHELF		-	X	X	X	-
DRAWERS DISPLAY SHELF		-	-	-	-	-
LOWER LEVEL DISPLAY SHELF		-				
FRONT GLASS		SINGLE				
LATERAL GLASS		SINGLE				
HOT SHELVES		OP.				
LIGHT COOLING SYSTEM		-				
CONTROL PANEL		ELECTRONIC THERMOSTAT + MECHANICAL				
COOLING SYSTEM		STATIC				
EVAPORATOR		1				
COMPRESSOR TYPE		HERMETIC				
CONDENSATION TYPE		AIR				
DEFROSTING TYPE		ELECTRIC				
EXTERNAL CONDENSATE DRAIN		-	-	OP.	OP.	-
CONDENSATE PAN		-	-	X	X	-
REMOTE COMPRESSOR TYPE		HERMETIC				

CONDENSATION TYPE		AIR				
DEFROSTING TYPE		ELECTRIC				
CE - GOST CERTIFICATION		-	X	X	X	-
CE - GOST POWER SUPPLY	V/ph/Hz	X				
ETL SAFETY SANITATION CERTIFICATION		-	-	-	-	-
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60				
WORKING TEMPERATURE		75 DEGREE F; 55% RH				
CLIMATIC CLASS		32°C 60% UR				

DRY HOT

MODULES		100	-	150	-	-
HEATED DISPLAY SHELF		X	-	x	-	-
FRONT GLASS		SINGLE				
LATERAL GLASS		SINGLE				
HALOGEN LAMPS		OPT				
HOT SHELVES		X				
CONTROL PANEL		ELECTRONIC THERMOSTAT				
CE - GOST CERTIFICATION		X	-	X	-	-
ETL SAFETY SANITATION CERTIFICATION	V/ph/Hz	220/1/60				
WORKING TEMPERATURE		+65°C				

BAIN-MARIE

MODULES		100	125	150	200	-
PANS		2*1/1	3*1/1	4*1/1	5*1/1	-
PAN DEPTH	[mm]	150				
FRONT GLASS		SINGLE				
LATERAL GLASS		SINGLE				
HALOGEN LAMPS		OPT				
HOT SHELVES		X				
WATER IN AND OUT		MANUAL				
CONTROL PANEL		MECHANICAL THERMOSTAT				
CE - GOST CERTIFICATION		X	X	X	X	-
ETL SAFETY SANITATION CERTIFICATION	V/ph/Hz	220/1/60				
WORKING TEMPERATURE		+65°C				