



## STRUCTURE

MODULES		100	150	200	250	S2-45	S2-90
LENGHT	[mm]	1000	1500	2000	2500	1014	2369
HEIGHT	[mm]	1351					
DEPTH	[mm]	1031					
END SIDE PANELS THICKNESS	[mm]	35					
WEIGHT	(kg)	222	290	386	375	200	375
POSSIBILITY TO JOIN WITH OTHER MODULES		X					
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM					
GLASS STRUCTURE		ALUMINIUM FINISH - GLASS OPEN UP-BOTTOM					
TRAY HOLDER		-					
WHEELS		OP.	OP.	OP.	OP.	OP.	OP.
SLIDING DOORS		X	X	X	X	X	X
CURTAIN		-	-	-	-	-	-
LIGHT		NEON					

## GELATO

MODULES		100	150	200	-	-	-
PAN DEPTH FROM - TO	[mm]	80 - 120	80 - 120	80 - 120	-	-	-
PAN 360*165	[nr]	-	-	-	-	-	-
PAN 360*250	[nr]	-	-	-	-	-	-
PAN 260*160	[nr]	10	16	22	-	-	-
PAN 180*160	[nr]	-	-	-	-	-	-
TRAPEZOIDAL PANS	[nr]	-	-	-	-	-	-
FRONT GLASS		SINGLE + SMALL SINGLE DEFLECTOR			-	-	-
LATERAL GLASS		GLASS			-	-	-
FLAVOUR MARKERS		SINGLE			-	-	-
SCOOP WASHER		X			-	-	-
CONTROL PANEL		OP.	OP.	OP.	-	-	-
4 SEASONS VERSION ( POS / NEG TEMP )		ELECTRONIC THERMOSTAT			-	-	-
DIFFERENTIATE TEMPERATURE		-	-	-	-	-	-
COOLING SYSTEM		-			-	-	-
AIR FLOW TYPE AND DIRECTION		VENTILATED			-	-	-
EVAPORATOR		SINGLE FROM CUSTOMER TO OPERATOR SIDE			-	-	-
COMPRESSOR TYPE		1			-	-	-
CONDENSATION TYPE		HERMETIC	HERMETIC	HERMETIC	-	-	-
DEFROSTING TYPE		AIR			-	-	-
EXTERNAL CONDENSATE DRAIN		HOT GAS			-	-	-
CONDENSATE PAN		OP.	OP.	OP.	-	-	-
REMOTE COMPRESSOR TYPE		X	X	X	-	-	-
		HERMETIC			-	-	-

CONDENSATION TYPE		AIR, WATER, MIXED AIR-WATER			-	-	-
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES			-	-	-
OIL SEPARATOR		OP.	OP.	OP.	-	-	-
CE - GOST CERTIFICATION		X	X	X	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	X			-	-	-
ETL SAFETY SANITATION CERTIFICATION		X	X	X	-	-	-
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60			-	-	-
WORKING TEMPERATURE		75 DEGREE F; 55% RH			-	-	-
CLIMATIC CLASS		35°C 60% UR			-	-	-

### PASTRY / DELI

<b>MODULES</b>		<b>100</b>	<b>150</b>	<b>200</b>	<b>250</b>	<b>S2-45</b>	<b>S2-90</b>
REFRIGERATED FIX DISPLAY SHELF		X	X	X	X	X	X
NEUTRAL FIX DISPLAY SHELF		X	X	X	X	X	X
DRAWERS DISPLAY SHELF		X	X	X	X	-	-
LOWER LEVEL DISPLAY SHELF		-					
FRONT GLASS		SINGLE + SMALL SINGLE DEFLECTOR GLASS					
LATERAL GLASS		SINGLE					
HOT SHELVES		OP.					
LIGHT COOLING SYSTEM		-					
CONTROL PANEL		ELECTRONIC THERMOSTAT					
COOLING SYSTEM		STATIC				VENTILATED	VENTILATED
EVAPORATOR		1					
COMPRESSOR TYPE		HERMETIC				HERMETIC	HERMETIC
CONDENSATION TYPE		AIR					
DEFROSTING TYPE		ELECTRIC				HOT GAS	
EXTERNAL CONDENSATE DRAIN		OP.	OP.	OP.	OP.	OP.	OP.
CONDENSATE PAN		X	X	X	X	X	X
REMOTE COMPRESSOR TYPE		HERMETIC				HERMETIC	
CONDENSATION TYPE		AIR					
DEFROSTING TYPE		ELECTRIC				HOT GAS 3 PIPES	
CE - GOST CERTIFICATION		X	X	X	X	X	X
CE - GOST POWER SUPPLY	V/ph/Hz	X					
ETL SAFETY SANITATION CERTIFICATION		X	X	X	X		
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	115/1/60				-	
WORKING TEMPERATURE		75 DEGREE F; 55% RH					
CLIMATIC CLASS		35°C 60% UR					

### PRALINE

<b>MODULES</b>		-	<b>150</b>	-	-	-	-
REFRIGERATED FIX DISPLAY SHELF		-	X	-	-	-	-
FRONT GLASS		SINGLE + SMALL SINGLE DEFLECTOR GLASS					
LATERAL GLASS		SINGLE					
LIGHT COOLING SYSTEM		OP.					
CONTROL PANEL		ELECTRONIC THERMOSTAT					
COOLING SYSTEM		STATIC					
EVAPORATOR		1					
COMPRESSOR TYPE		HERMETIC					
CONDENSATION TYPE		AIR					
DEFROSTING TYPE		PAUSA					
EXTERNAL CONDENSATE DRAIN		-	OP.	-	-	-	-
CONDENSATE PAN		-	X	-	-	-	-
REMOTE COMPRESSOR TYPE		-	-	-	-	-	-
CONDENSATION TYPE		-	-	-	-	-	-
DEFROSTING TYPE		-	-	-	-	-	-
CE - GOST CERTIFICATION		-	X	-	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	X					
WORKING TEMPERATURE		75 DEGREE F; 55% RH					
CLIMATIC CLASS		35°C 60% UR					

### DRY HOT

<b>MODULES</b>		<b>100</b>	<b>150</b>	-	-	-	-
HEATED DISPLAY SHELF		X	X	-	-	-	-
FRONT GLASS		SINGLE					
LATERAL GLASS		SINGLE					
HALOGEN LAMPS		SPECIAL					
HOT SHELVES		-					
CONTROL PANEL		MECHANIC THERMOSTAT					

CE - GOST CERTIFICATION		X	X	-	-	-	-
CE - GOST POWER SUPPLY	V/ph/Hz	220/1/60					
WORKING TEMPERATURE		+65°C					
<b>BREAD</b>							
<b>MODULES</b>		-	<b>150</b>	<b>200</b>	<b>250</b>	-	-
FIXED DISPLAY SHELF		-	X	X	X	-	-