

# SPECIAL



## STRUCTURE

MODULES		110	160	210	320
LENGTH	[mm]	1100	1600	2100	3200
HEIGHT	[mm]	1316			
DEPTH	[mm]	1178			
END SIDE PANELS THICKNESS	[mm]	50			
WEIGHT	[kg]	240	335	425	550
POSSIBILITY TO JOIN WITH OTHER MODULES		-			
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM			
GLASS STRUCTURE		NO - GLASS OPEN UP - BOTTOM			
TRAY HOLDER		-			
WHEELS		OP.	OP.	OP.	OP.
SLIDING DOORS		X	X	X	X
CURTAIN		OP.	OP.	OP.	OP.
LIGHT		NEON			

## GELATO

MODULES		110	160	210	320
PAN DEPTH FROM - TO	[mm]	80 - 150	80 - 150	80 - 150	80 - 150
PAN 360*165	[nr]	12	18	24	36
PAN 360*250	[nr]	8	12	16	24
PAN 260*160	[nr]	-	-	-	-
PAN 180*160	[nr]	-	-	-	-
TRAPEZOIDAL PANS	[nr]	-	-	-	-
FRONT GLASS		DOUBLE HEATED			
LATERAL GLASS		HEATED STRATIFIED			
FLAVOUR MARKERS		X			
SCOOP WASHER		OP.	OP.	OP.	OP.
CONTROL PANEL		ELECTRONIC THERMOSTAT			
4 SEASONS VERSION ( POS / NEG TEMP )		OP.	OP.	OP.	OP.
DIFFERENCIATE TEMPERATURE		3+3	3+3	3+3	9+9
COOLING SYSTEM		VENTILATED			
AIR FLOW TYPE AND DIRECTION		SINGLE FROM OPERATOR TO CUSTOMER SIDE			
EVAPORATOR		1 ( OPT 2 )			
COMPRESSOR TYPE		HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC	SEMI-HERMETIC

CONDENSATION TYPE		AIR			
DEFROSTING TYPE		HOT GAS			REVERSE CYCLE
EXTERNAL CONDENSATE DRAIN		X	X	X	X
CONDENSATE PAN		OP.	OP.	OP.	OP.
REMOTE COMPRESSOR TYPE		-	-	-	-
CONDENSATION TYPE		-	-	-	-
DEFROSTING TYPE		-	-	-	-
OIL SEPARATOR		OP.	OP.	OP.	OP.
CE - GOST CERTIFICATION		X	X	X	X
CE - GOST POWER SUPPLY	V/ph/Hz	X			
ETL SAFETY SANITATION CERTIFICATION		X	X	X	
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60			-
WORKING TEMPERATURE		75 DEGREE; 55% RH			
CLIMATIC CLASS		35°C 60% UR			