



## STRUCTURE

MODULES		1350-ROUND	1500
LENGHT	[mm]	1350	1500
HEIGHT	[mm]		1003
DEPTH			1405
END SIDE PANELS THICKNESS			-
WEIGHT			FROM 350 TO 480
POSSIBILITY TO JOIN WITH OTHER MODULES			-
TANK		FOAM TANK INJECTED WITH POLYURETHAN AT 40KG/CM	
GLASS STRUCTURE			-
TRAY HOLDER			-
WHEELS			OP.
SLIDING DOORS			-
CURTAIN			-
LIGHT			NEON/LED

## GELATO

MODULES	[mm]	1350-ROUND	1500
PAN DEPTH FROM - TO	[mm]		120 - 150
PAN 360*165	[nr]		-
PAN 360*250	[nr]		-
PAN 260*160	[nr]		-
PAN 180*160	[nr]		-
TRAPEZOIDAL PANS	[nr]		12-15-18
OPERATOR GLASS			DOUBLE HEATED
CUSTOMER GLASS			DOUBLE HEATED
FLAVOUR MARKERS			X
SCOOP WASHER			OP.
CONTROL PANEL			ELECTRONIC THERMOSTAT
4 SEASONS VERSION ( POS / NEG TEMP )			OP.
DIFFERENCIATE TEMPERATURE			-
COOLING SYSTEM			VENTILATED
AIR FLOW TYPE AND DIRECTION			SINGLE FROM EXTERNAL TO INTERNAL PEREMETER

EVAPORATOR		2
COMPRESSOR TYPE		HERMETIC
CONDENSATION TYPE		AIR
DEFROSTING TYPE		HOT GAS
EXTERNAL CONDENSATE DRAIN		OP.
CONDENSATE PAN		X
REMOTE COMPRESSOR TYPE		SEMI-HERMETIC
CONDENSATION TYPE		AIR, WATER, AIR-WATER MIXED
DEFROSTING TYPE		REVERSE CYCLE 2 PIPES
OIL SEPARATOR		OP.
CE - GOST CERTIFICATION		X
CE - GOST POWER SUPPLY	V/ph/Hz	X
ETL SAFETY SANITATION CERTIFICATION		X
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	208-220/1/60
WORKING TEMPERATURE		75 DEGREES F: 55% RH
CLIMATIC CLASS		35°C 60% UR

### **PASTRY/PRALINE**

<b>MODULES</b>		<b>1350-ROUND</b>	<b>1500</b>
ROTATING DISPLAY SHELF			X
OPERATOR GLASS		DOUBLE HEATED	
CUSTOMER GLASS		DOUBLE HEATED	
LIGHT CHILLER		-	
CONTROL PANEL		ELECTRONIC THERMOSTAT WITH HUMIDITY SENSOR	
COOLING SYSTEM		VENTILATED	
EVAPORATOR		1	
COMPRESSOR TYPE		HERMETIC	
CONDENSATION TYPE		AIR	
DEFROSTING TYPE		AT STOP	
EXTERNAL CONDENSATE DRAIN		OP.	
CONDENSATE PAN		X	
REMOTE COMPRESSOR TYPE		HERMETIC	
CONDENSATION TYPE		AIR, WATER, AIR-WATER MIXED	
DEFROSTING TYPE		AT STOP	
CE - GOST CERTIFICATION		X	
ETL SAFETY SANITATION POWER SUPPLY	V/ph/Hz	220/1/60	
WORKING TEMPERATURE		75 DEGREES F: 55% RH	
CLIMATIC CLASS		35°C 60% UR	

